

R76ATR



Tire Changer

SKU# 5140140

Tilt Back, Right-Tower Single Assist, 30" Capacity, 3 HP, 220V, 1-Phase, 50/60hz

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Tilt-Tower Tire Changer Design for a Smaller Footprint

The Ranger R76ATR [tire changer](#) is easy to operate, rugged enough to stand up to demanding workloads and comes equipped with power assist tower tools to help when mounting low-profile performance tires. A large 30" capacity turntable features adjustable, hardened-steel RimGuard™ wheel clamps. These provide an internal clamping capacity of 9"- 28" and external clamping capacity of 10"- 30".

Specifications

Motor	3 HP (220 VAC 50-60 HZ)
Drive System Type	Electric / Hydraulic
Air Requirement	110-175 PSI (8-12 BAR)
Wheel Clamping Method	4 Clamps - Internal / External
Table Clamping System	Dual Pneumatic Cylinders
Bead Breaking System	Adjustable Pneumatic Blade
Tower Design	Tilt-Back
Power Assist Tower(s)	Single / Right-Side
Bead Lifting Roller(s)	Single / Right-Side
Upper Bead Assist Roller	Single / Right-Side
Vertical Shaft / Tool Head	Pneumatic / Locking
Powerful Bead Seating System	TurboBlast™
Internal Rim Clamping Capacity	10" - 30" (254 mm - 762 mm)
External Rim Clamping Capacity	9" - 28" (229 mm - 711 mm)
Turntable Tire Width Capacity (Mounting)	4" - 18" (102 mm - 457 mm)
Bead Breaker Tire Width Capacity (Demounting)	1.5" - 16" (38 mm - 406 mm)
Maximum Tire Diameter	43" (1,092 mm)
Shipping Weight	970 lbs. (440 kg)



Standard Features

- Traveling Drop-Center
- Hold Down Device
- Inflation System
- Inflation Gauge & Air Dump Valve
- Inflation Pressure Regulator/Limiter
- Oiler / Lubricator
- Air Regulator
- Bead Tool/Tire Iron
- Alloy-Steel Mount-Demount Head
- Nylon Mount-Demount Head
- Large Soap Bucket
- Soap Brush