

XPR-12CL



Two-Post Lifts

SKU# 5175405

12,000-lb. Capacity, Clearfloor, Triple-Telescoping Arms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

XPR-12CL Two-Post Lift Offers Heavy-Duty Lifting Capability

Every XPR-12CL [two-post lift](#) is designed to keep your floor clean—no visible cables or airlines. Our Clearfloor design offers enough space for vehicles up to 12,000 lbs. Pure Direct-Drive performance is matched by, cutting-edge technology, top-of-the-line materials and a design that's ahead of its time. This car lift fits in shops with ceilings higher than 14' and won't crowd your floor while you work beneath a vehicle.



Options

SKU#	Model	Description
5175410	XPR-12CL-LWB	Long-Reach Arms
5175407	XPR-12CL-192	192" Overall Height
5175415	XPR-12CL-192-LWB	192" OAH / Long-Reach

Features

- CE Approved and Certified. Meets or exceeds the standards prescribed by European Standard EN 1493
- Padded overhead safety shutoff bar
- Extended height top-beam provides greater clearance
- Single-point safety release
- Dual direct-drive hydraulic cylinders
- Dual-synchro equalization system for equal lifting
- Oversized 53" tall carriage for superior strength
- Electric / hydraulic power system
- Oversized A36 steel base plates
- Self-lubricating dura-glide UHMW polyethylene bearings
- Safety locks in each column spaced every 3"
- Automatic arm restraints
- Heavy-duty 1/2" aircraft-quality equalizer cables
- Oversized cable sheave diameter reduces cable fatigue
- Durable, rubber lift pads with stackable adapters
- 16-piece specialty adapter set includes four 6" stackable adapters, four 3" stackable adapters, four polyurethane contact pads and four frame cradle pads
- Convenient storage is included for truck and van adapters
- Triple-telescoping arms provide increased range

Quality Assurance for Heavy-Duty Lifting

When you buy BendPak, you can expect a significant boost in performance and lift operation life expectancy because your lift is built to be the last one you ever purchase. No one surpasses us in quality and safety. That's why when you get one of our lifts, you get more than just a great product. You get peace of mind. That's the benefit of owning a BendPak.

Triple-telescoping arm set

Three-stage front and three-stage rear arms provide greater maximum reach, as well as superior minimum retraction. Use this super-duty lift system for raising standard passenger vehicles and heavy-duty trucks.

Optional column extension

BendPak can increase your overhead clearance to maximize the number vehicle types you can service in this weight class.

High-speed hydraulics

Free-flow, high-pressure 3/8" hydraulic lines, a high-flow pump and integrated AC power-unit increase ascent and descent speeds for enhanced productivity.

Extended Height

The safe and rugged XPR-12C-192 two-post lift features extended height columns for added overhead clearance, as well as an adjustable top beam to accommodate wide or narrow installation setups.

Specifications

Model	XPR-12CL	XPR-15CL	XPR-18CL
SKU#	5175405	5175408	5175409
Lifting Capacity	12,000 lbs. (5,443 kg)	15,000 lbs. (6,804 kg)	18,000 lbs. (8,165 kg)
A - Rise	69" (1,753 mm)	69" (1,753 mm)	69" (1,753 mm)
B - Rise + Pad Only	74" (1,880 mm)	74" (1,880 mm)	74" (1,880 mm)
C - Max. Lifting Height	80" (2,032 mm)	80" (2,032 mm)	80" (2,032 mm)
D - Min. Height + Pad	5" (127 mm)	5" (127 mm)	5" (127 mm)
E - Height Overall (*)	170" (4,318 mm)	170" (4,318 mm)	170" (4,318 mm)
F - Width Overall	155" (3,937 mm)	155" (3,937 mm)	155" (3,937 mm)
G - Outside Columns	144" (3,658 mm)	144" (3,658 mm)	144" (3,658 mm)
H - Inside Columns	120" (3,048 mm)	120" (3,048 mm)	120" (3,048 mm)
I - Drive-Thru Clearance	106" (2,692 mm)	106" (2,692 mm)	106" (2,692 mm)
J - Floor to Top Switch (*)	165" (4,191 mm)	165" (4,191 mm)	165" (4,191 mm)
K - Front Arm Reach (MAX)	32" (813 mm)	39" (991 mm)	39" (991 mm)
K - Front Arm Reach (MIN)	60" (1,524 mm)	60" (1,524 mm)	60" (1,524 mm)
L - Rear Arm Reach (MAX)	32" (813 mm)	39" (991 mm)	39" (991 mm)
L - Rear Arm Reach (MIN)	60" (1,524 mm)	60" (1,524 mm)	60" (1,524 mm)
Screw Pad Adjustment	Not Compatible	Not Compatible	Not Compatible
Max. Load per Arm	3,000 lbs. (1,361 kg)	3,750 lbs. (1,701 kg)	4,500 lbs. (2,041 kg)
Time to Full Rise	45 seconds	45 seconds	45 seconds
Noise	45 dB	45 dB	45 dB
Motor	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph	220 VAC / 60 Hz / 1 Ph

*Optional bolt-on top extension for columns raises the overall height and overhead safety bar an additional 24". Must be ordered from BendPak at time of order.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for a complete list or contact BendPak via contact@bendpak.com.

